



DATE ВΥ

CERTIFIED

SPECIFICATIONS PRODUCT CODE: LB008	TIONS	
PARAMETER	STANDARD	AS-CONFIGURED
CAPACITY (US TON)	3/4	STD,
LIFT (FT.)	5	STD,
MINIMUM HEADROOM, C (IN.)	11.0	STD.
LOAD CHAIN DIA. (mm) X CHAIN FALL LINES	5.6 X 1	STD.
NET WEIGHT (LBS.)	13	STD.
PULL TO LIFT LOAD (LBS.)	54	STD.
WEIGHT FOR ADD. ONE FOOT OF LIFT (LBS.)	0.5	STD.

- NOTES:

 1.) CAD COMPUTER FILE NOT DRAWN TO SCALE.

 HARD COPY SCALED TO FIT PAPER SIZE.

 2.) DRAWING SUBJECT TO CHANGE WITHOUT NOTICE.

ANGULAR: +/- 1°	FRACTIONAL +/- 1/32"	DECIMAL: $+/-$ X.XX = .01 $+/-$ X.X = .05	TOLERANCES (EXCEPT AS NOTED)	NC.
	"IAL	x = 01	ANCES (S NOTED)	
СНК'D ВҮ: ЕМ	DRAWN BY: MJS		L	INTERIOR DESCRIPTION
DATE: 2/3/03	SEE NOTE 1	HOISTS AND CRANES	LB008 LEVER CHAIN HOIST L5 SERIES	ION
5	DRAWING NO:	CRANES	CHAIN I RIES	DISTANTA
56130))		HOIST	מוצמונים מאור מוורמונים מו
0	REV. NO.			2001