



**SPARTAN**  
SCIENTIFIC

# 3825 Series Valves



Part no. **3825-66-B20Y-A**



Part no. **3825-66-B20G-A**

3825 series valves are 2-way, normally closed, direct acting valves. The engineered composite body material and other wetted materials are suitable for potable water applications.

## Features

- Direct acting operator
- Glass reinforced Nylon body
- Port size 1/4 push to connect tubing
- 2-way, 2-position normally closed operation
- 24 VDC or 120 VAC (other voltage coils available)

3825 Series Solenoid Valves										
Part No.	Price	Ports	Cv	Max Pressure	Operating Voltage	Connection	Weight (lbs)	Drawing Link	Vendor Specs	Vendor Application and Install Guide
<a href="#">3825-66-B20Y-A</a>	\$58.00	1/4in push-to-connect tubing inlet(s), 1/4in push-to-connect tubing outlet(s)	0.24	150 psi	120VAC	11mm DIN style wiring plug	0.23	<a href="#">PDF</a>	PDF	PDF
<a href="#">3825-66-B20U-A</a>	\$58.00				24VDC		0.23	<a href="#">PDF</a>		
<a href="#">3825-67-B20Y-A</a>	\$63.00		0.31	75 psi	120VAC	18mm DIN style wiring plug	0.23	<a href="#">PDF</a>		
<a href="#">3825-67-B20U-A</a>	\$63.00				24VDC		0.23	<a href="#">PDF</a>		
<a href="#">3825-66-B20G-A</a>	\$57.00		0.24	150 psi	120VAC	18in pigtail (PVC 22AWG multi-strand copper wire 300 Volt)	0.23	<a href="#">PDF</a>		
<a href="#">3825-66-B20C-A</a>	\$57.00				24VDC		0.23	<a href="#">PDF</a>		
<a href="#">3825-67-B20G-A</a>	\$62.00		0.31	75 psi	120VAC	18in pigtail (PVC 22AWG multi-strand copper wire 300 Volt)	0.23	<a href="#">PDF</a>		
<a href="#">3825-67-B20C-A</a>	\$62.00				24VDC		0.23	<a href="#">PDF</a>		